

# Safety data sheet

## ELASTOSPRAY 81302 R RESIN

Revision date : 2004/06/17  
Version: 1.0

Page: 1/5  
(30231252/MDS\_GEN\_US/EN)

### 1. Substance/preparation and company identification

Company  
BASF Corporation  
3000 Continental Drive - North  
Mount Olive, NJ 07828-1234

24 Hour Emergency Response Information  
CHEMTREC: (800) 424-9300  
BASF HOTLINE: (800) 832-HELP

Chemical family: resin  
Synonyms: Urethane System Resin Component

### 2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
	< 70.0 %	Polyol
	< 20.0 %	Flame Retardant
	< 1.0 %	Catalyst
108-01-0	< 3.0 %	2-dimethylaminoethanol
	< 1.0 %	Surfactant
460-73-1	< 12.0 %	Propane, 1,1,1,3,3-pentafluoro-

### 3. Hazard identification

#### Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.  
CAN CAUSE NERVOUS SYSTEM DAMAGE.  
SENSITIZER.  
CORROSIVE TO SKIN.

#### Potential health effects

##### **Primary routes of exposure**

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

##### **Acute toxicity:**

Ingestion may cause gastrointestinal disturbances.

##### *Information on: Fluorocarbons*

*At levels above the recommended exposure limit, the fluorocarbon acts as a weak narcotic. Acute overexposure causes tremors, confusion, irritation, suffocation, and may result in cardiac sensitization.*

##### *Information on: Dimethylaminoethanol*

*Dimethylaminoethanol is extremely irritating to the skin and eyes. Direct contact with the liquid is corrosive. Acute inhalation exposures at high concentrations have been known to produce respiratory difficulties, loss of coordination and decreased motor activity in rats.*

##### **Irritation:**

Irritating to respiratory system.

##### *Information on: Polyol*

*Contact with the eyes and skin may result in irritation.*

# Safety data sheet

## ELASTOSPRAY 81302 R RESIN

Revision date : 2004/06/17

Page: 2/5

Version: 1.0

(30231252/MDS\_GEN\_US/EN)

*Information on: Dimethylaminoethanol*

*Contact with dimethylaminoethanol may result in severe irritation. Burns and permanent injury may result.*

**Repeated dose toxicity:**

No other known chronic effects.

*Information on: Dimethylaminoethanol*

*Repeated skin contact with dimethylaminoethanol may result in sensitization. Repeated inhalation has been known to produce effects on the eyes and nasal mucosa as well as respiratory and olfactory lesions in experimental animals. Exposure to dimethylaminoethanol has been associated with visual and ocular changes and is reversible upon significantly reduced or ceased exposure.*

---

### 4. First-aid measures

**General advice:**

Remove contaminated clothing.

**If inhaled:**

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

**If on skin:**

Wash affected areas thoroughly with soap and water. Immediate medical attention required.

**If in eyes:**

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

**If swallowed:**

Rinse mouth and then drink plenty of water. Induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

---

### 5. Fire-fighting measures

Flash point: approx. 120 °C (closed cup)  
Autoignition: No data available.

**Suitable extinguishing media:**

water, dry extinguishing media, carbon dioxide, foam

**Hazards during fire-fighting:**

No particular hazards known.

**Protective equipment for fire-fighting:**

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

---

### 6. Accidental release measures

**Cleanup:**

Spills should be contained, solidified, and placed in suitable containers for disposal.

---

# Safety data sheet

## ELASTOSPRAY 81302 R RESIN

Revision date : 2004/06/17  
Version: 1.0

Page: 3/5  
(30231252/MDS\_GEN\_US/EN)

### 7. Handling and storage

#### Handling

**Protection against fire and explosion:**

No explosion proofing necessary.

#### Storage

**General advice:**

Product that is frozen and/or tending to sedimentation can be liquified or homogenized by careful application of indirect heat (do not use flames or direct contact with a heat source). Protect from direct sunlight. Keep in a cool, well-ventilated place. Avoid extreme heat. Store protected against freezing. Stored and transported in a cylinder under pressure. Must not be repacked by the customer.

**Storage stability:**

Storage temperature: 70 - 80 °F

Protect against moisture. Store in unopened original containers in a cool and dry place.

### 8. Exposure controls and personal protection

**Advice on system design:**

Provide local exhaust ventilation to control vapours/mists.

#### Personal protective equipment

**Respiratory protection:**

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

**Hand protection:**

Chemical resistant protective gloves

**Eye protection:**

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

**General safety and hygiene measures:**

Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice. Wear protective clothing as necessary to prevent contact. Avoid inhalation of vapours/mists. Wash soiled clothing immediately.

### 9. Physical and chemical properties

Form:	liquid	
Odour:	ether-like	
Colour:	dark amber	
pH value:	>= 7	
Bulk density:	9.20 lb/USg	
Miscibility with water:		slightly soluble

### 10. Stability and reactivity

**Conditions to avoid:**

> 80 degrees Fahrenheit

Avoid moisture. Avoid direct sunlight. Avoid excessive temperatures.

# Safety data sheet

## ELASTOSPRAY 81302 R RESIN

Revision date : 2004/06/17  
Version: 1.0

Page: 4/5  
(30231252/MDS\_GEN\_US/EN)

**Hazardous reactions:**

The product is chemically stable.

**Decomposition products:**

Hazardous decomposition products: carbon monoxide, carbon dioxide

**Thermal decomposition:**

No data available.

**Corrosion to metals:**

No corrosive effect on metal.

---

### 11. Toxicological information

---

### 12. Ecological information

---

### 13. Disposal considerations

**Waste disposal of substance:**

Incinerate in a licensed facility.  
Dispose of in a licensed facility.  
Do not discharge substance/product into sewer system.

**Contaminated packaging:**

Return to the manufacturer with residual pressure. If cylinder is damaged, please contact supplier. Empty cylinders (all sizes) must be depressurized before they are returned to supplier. Depressurization will not relieve all pressure. Always seal cylinder valves for return.  
Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Refer to 40 CFR § 261.7 (residues of hazardous waste in empty containers).  
Decontaminate containers prior to disposal. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

---

### 14. Transport information

Reference Bill of Lading

---

### 15. Regulatory information

**Federal Regulations****Registration status:**

TSCA, US released / listed

**State regulations**

State RTK

CAS Number

Chemical name

State RTK

# Safety data sheet

## ELASTOSPRAY 81302 R RESIN

Revision date : 2004/06/17

Page: 5/5

Version: 1.0

(30231252/MDS\_GEN\_US/EN)

108-01-0

2-dimethylaminoethanol

MA, NJ, PA

**CA Prop. 65:**

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

---

### 16. Other information

**HMIS III rating**

Health: 1      Flammability: 1      Physical hazard: 1

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

---

**Local contact information**

William Robert  
1-734-324-5244

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET